

according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Revision date: 06.04.2020

Page 1 of 9

1. Identification

Product identifier

ANSI / ASHRAE Standard 52.2P Test Dust

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

test dust

Details of the supplier of the safety data sheet

Company name:	Powder Technology Inc.
Street:	1300 Grey Fox Road
Place:	USA-55112 Arden Hills, MN
Telephone:	+1 952 894 -8737
e-mail:	sales@powdertechnologyinc.com
Internet:	http://www.powdertechnologyinc.com
Emergency phone number:	+1 952 894 -8737

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Carcinogenicity: Carc. 2 Specific target organ toxicity repeated or prolonged exposure: STOT RE 1

Label elements

29 CFR Part 1910.1200

Danger

Signal word: Pictograms:



Hazard statements

Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If exposed or concerned: Get medical advice/attention.

Store locked up.

Hazards not otherwise classified

The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

3. Composition/information on ingredients

<u>Mixtures</u>

Page 2 of 9



Safety Data Sheet

according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Revision date: 06.04.2020

Chemical characterization

Powder-Sand, Fibres (Second-cut cotton linters (cellulose))

Mineral bound: Aluminium oxide; Alumina CAS No. 1344-28-1

potassium oxide (mineral) CAS No. 12136-45-7

sodium oxide (mineral) CAS No. 1313-59-3

Iron (III) oxide (hematite) CAS No. 1309-37-1

Magnesium oxide CAS No. 1309-48-4

Hazardous components

CAS No	Components	Quantity
14808-60-7	Silica (fine dust)	65 - 70 %
1305-78-8	calcium oxide (mineral)	2,5 - 4 %
13463-67-7	titanium dioxide	< 1 %

4. First-aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Provide fresh air. In case of irregular breathing or respiratory arrest provide artificial respiration. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Wash with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.



according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Revision date: 06.04.2020

Page 3 of 9

Dry extinguishing powder. Foam. Water. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the chemical

Non-flammable. The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

In case of fire: Carbon dioxide (CO2), Carbon monoxide (CO), Gases/vapours, irritant.

Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Knock down dust with water spray jet. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition - No smoking. Provide adequate ventilation. Avoid dust formation. Do not breathe dust. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove persons to safety.

Environmental precautions

No special environmental measures are necessary.

Methods and material for containment and cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid dust formation. Do not breathe dust. Wear personal protection equipment. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention. The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

Do not store together with: Hydrofluoric acid; Fluorine; Oxidising agent, strong; Acid, concentrated.

8. Exposure controls/personal protection

Control parameters



according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Page 4 of 9

Revision date: 06.04.2020

Exposure limits

CAS No.	Substance	ppm	mg/m³	f/cc	Category	Origin
1305-78-8	Calcium oxide	-	5		TWA (8 h)	PEL
		-	2		TWA (8 h)	REL
			2		TWA (8 h)	ACGIH-2019
9004-34-6	Cellulose (total)	-	10		TWA (8 h)	REL
9004-34-6	Cellulose Respirable fraction	-	5		TWA (8 h)	PEL
9004-34-6	Cellulose Total dust	-	15		TWA (8 h)	PEL
9004-34-6	Cellulose		10		TWA (8 h)	ACGIH-2019
1309-37-1	Iron oxide (Fe2O3) (respirable fraction)		5		TWA (8 h)	ACGIH-2019
1309-37-1	Iron oxide dust and fume (as Fe)	-	5		TWA (8 h)	REL
1309-37-1	Iron oxide fume	-	10		TWA (8 h)	PEL
1309-48-4	Magnesium oxide (inhalable fraction)		10		TWA (8 h)	ACGIH-2019
1309-48-4	Magnesium oxide fume Total Particulate	-	15		TWA (8 h)	PEL
14808-60-7	Silica, crystalline (as respirable dust)	-	0.05		TWA (8 h)	REL
14808-60-7	Silica, crystalline - alpha-quartz (respirable fraction)		0.025		TWA (8 h)	ACGIH-2019
14808-60-7	Silica, crystalline quartz, respirable dust	(Z-3)	(Z-3)		TWA (8 h)	PEL
14808-60-7	Silica, crystalline quartz, total dust	-	(Z-3)		TWA (8 h)	PEL
13463-67-7	Titanium dioxide Total dust	-	15		TWA (8 h)	PEL
13463-67-7	Titanium dioxide		10		TWA (8 h)	ACGIH-2019
1344-28-1	alpha-Alumina Respirable fraction	-	5		TWA (8 h)	PEL
1344-28-1	alpha-Alumina Total dust	-	15		TWA (8 h)	PEL

Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Do not breathe dust. Avoid dust formation. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

Eye/face protection

Wear eye protection/face protection.

Suitable eye protection: Dust protection goggles.

Hand protection

Wear suitable gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at:



according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Page 5 of 9

Revision date: 06.04.2020

Generation/formation of dust.

Suitable respiratory protective equipment: particulates filter device (DIN EN 143). Filtering device (full mask or mouthpiece) with filter: FFP2 / N95; High efficiency particulate air filter (HEPA filter).

Environmental exposure controls

No special environmental measures are necessary.

9. Physical and chemical properties

Information on basic physical and chemica	al properties	
Physical state:	solid	
Color:	grey	
Odor:	odourless	
pH-Value:	not determined	
Changes in the physical state		
Melting point/freezing point:	not determined	
Initial boiling point and boiling range:	2980 °C	
Flash point:	210 °C	
Flammability		
Solid:	not determined	
Gas:	not applicable	
Explosive properties The product is not: Explosive. The pro of fine dust however leads to the dang	oduct in the delivered form is not dust explosion capat ger of dust explosion.	ole; the enrichment
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Ignition temperature:	not determined	
Auto-ignition temperature		
Solid:	407 °C	
Gas:	not applicable	
Decomposition temperature:	not determined	
Oxidizing properties Not oxidising.		
Vapor pressure: (at 20 °C)	not determined	
Density:	~2 g/cm³	
Water solubility:	Immiscible	
Solubility in other solvents not determined		
Partition coefficient:	not determined	
Viscosity / dynamic:	not applicable	
Viscosity / kinematic:	not applicable	
Vapor density:	not determined	
Evaporation rate:	not determined	
Other information		
Solid content:	100,00 %	
Odour threshold: not applicable		



according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Revision date: 06.04.2020

10. Stability and reactivity

Reactivity

No hazardous reaction when handled and stored according to provisions.

Chemical stability

Stability:

Stable

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Hazardous reactions:

Will not occur

Explosive reaction with: Hydrofluoric acid; Fluorine. The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to

the danger of dust explosion.

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

Hydrofluoric acid; Fluorine; Oxidising agent, strong; Acid, concentrated.

Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Gas/vapours, irritant.

11. Toxicological information

Information on toxicological effects

Route(s) of Entry

Inhalation, oral, Eye contact, dermal.

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer (titanium dioxide) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. Contains: Silica (fine dust).

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure

Causes damage to organs through prolonged or repeated exposure (Silica (fine dust)) Extended inhalation at levels above the workplace limit value can cause irreversible damage to the lungs (silicosis). A repeated, excessive dust exposure can cause pneumoconiosis. Inhalation of dust may cause irritation of the respiratory system.

Carcinogenicity (OSHA):	No ingredient of this mixture is listed.
Carcinogenicity (IARC):	Silica dust, crystalline, in the form of quartz or cristobalite (CAS 14808-60-7) is
	listed in group 1. Ferric oxide (CAS 1309-37-1) is listed in group 3. Titanium
	dioxide (CAS 13463-67-7) is listed in group 2B.
Carcinogenicity (NTP):	No ingredient of this mixture is listed.

Aspiration hazard

Based on available data, the classification criteria are not met.

Page 6 of 9



according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Revision date: 06.04.2020

Additional information on tests

The mixture is classified as hazardous according to Directive 1999/45/EC. Special hazards arising from the substance or mixture!

Further information

Inhalation of dust may cause irritation of the respiratory system. The following symptoms may occur: Respiratory complaints, Cough.

Extended inhalation at levels above the workplace limit value can cause irreversible damage to the lungs (silicosis). Symptoms: Respiratory complaints, Fever, Cough. acute Symptoms: Fatal if inhaled.

Skin contact: slightly irritant but not relevant for classification. After eye contact: slightly irritant but not relevant for classification.

After ingestion: Gastrointestinal complaints, Nausea, Vomiting.

12. Ecological information

Ecotoxicity

The product is not: Ecotoxic.

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

Mobility in soil

The product has not been tested.

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Dispose of waste according to applicable legislation.

14. Transport information

US DOT 49 CFR 172.101

Proper shipping name:	Not a hazardous material with respect to these transport regulations.
Marine transport (IMDG)	
<u>UN number:</u>	No dangerous good in sense of this transport regulation.
UN proper shipping name:	No dangerous good in sense of this transport regulation.
Transport hazard class(es):	No dangerous good in sense of this transport regulation.
Packing group:	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
UN number:	No dangerous good in sense of this transport regulation.
UN proper shipping name:	No dangerous good in sense of this transport regulation.
Transport hazard class(es):	No dangerous good in sense of this transport regulation.
Packing group:	No dangerous good in sense of this transport regulation.
Environmental hazards	

Page 7 of 9



Revision date: 06.04.2020

Safety Data Sheet

according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Page 8 of 9

ENVIRONMENTALLY HAZARDOUS:

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no

not applicable

15. Regulatory information

U.S. Regulations

National Inventory TSCA

CAS No. 14808-60-7: Yes. CAS No. 13463-67-7: Yes. CAS No. 1305-78-8: Yes. CAS No. 1333-86-4: Yes. CAS No. 9004-34-6: Yes. CAS No. 1344-28-1: Yes. CAS No. 12136-45-7: Yes. CAS No. 1313-59-3: Yes. CAS No. 1309-37-1: Yes. CAS No. 1309-48-4: Yes.

National regulatory information

SARA Section 311/312 Hazards:

Silica (fine dust) (14808-60-7): Delayed (chronic) health hazard calcium oxide (mineral) (1305-78-8): Immediate (acute) health hazard titanium dioxide (13463-67-7): Delayed (chronic) health hazard

SARA Section 313 Toxic release inventory:

Aluminum oxide (fibrous forms) (1344-28-1): De minimis limit = 1.0 %, Reportable threshold = Standard

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information

Hazardous Materials Informatio	n Label (HMIS)
Health:	*2
Flammability:	1
Physical Hazard:	0
NFPA Hazard Ratings	
Health:	2
Flammability:	1
Reactivity:	1
Unique Hazard:	
Revision date:	06.04.2020
Revision No:	1,00
Abbreviations and acronyms	
ACGIH: American Conference	e of Governmental Industrial Hygienists

CFR: Code of Federal Regulations DOT: Department of Transportation

ICAO: International Civil Aviation Organization

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods





according to 29 CFR 1910.1200(g)

ANSI / ASHRAE Standard 52.2P Test Dust

Revision date: 06.04.2020

Page 9 of 9

IARC: International Agency for Research on Cancer GHS: Globally Harmonized System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service NFPA: National Fire Protection Association NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration PEL: permissible exposure limit REL: recommended exposure limit SARA: Superfund Amendments and Reauthorization Act STEL: Short-term exposure limit TSCA: Toxic Substances Control Act TWA: time-weighted average TI: Technical Instructions DGR: Dangerous Goods Regulations **UN: United Nations** ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)